

Specificatieblad


valid from: 4-1-16



tankaansluiting PVC-U metrisch, met 3-delige koppeling met spie-eind/reductiemof

uitvoering:

- afdichting: vlakke pakking EPDM
- onderlegging: PP
- vervangingsonderdelen op aanvraag



d (mm)	d1 (mm)	Code	SP	gewicht (kg)
20	25	161 050 206	0	0,046
25	32	161 050 207	50	0,066
32	40	161 050 208	50	0,106
40	50	161 050 209	35	0,190
50	63	161 050 210	25	0,248
63	75	161 050 211	15	0,352
75	90	161 050 212	20	0,539
90	110	161 050 213	10	1,083
110	125	161 050 214	6	1,350

d (mm)	L3 max (mm)	gat in tankwand (mm)	G (inch)	L1 (mm)	L2 (mm)	L (mm)	L4 (mm)	s (mm)	M
20	23	28	¾	13	19	42	16	32	
25	23	35	1	15	22	45	19	40	
32	24	43	1 ¼	17	26	49	22	50	
40	21	55	1 ¾	19	31	48	26	60	
50	21	61	2	21	38	52	31	69	
63	23	77	2 ½	23	44	53	38	85	
75	20	89	3	26	51	56	44	100	
90	20	115		32	61	62	51	125	M113
110	22	135		36	69	66	61	147	M133

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>