


Specificatieblad

valid from: 26-2-16



mof, ABS metrisch

- > d225 - maximum temperatuur: +40°C

d (mm)	PN (bar)	Code	SP	gewicht (kg)	D (mm)	L (mm)	z (mm)	inch bena- dering (inch)
20	16	729 910 106	10	0,007	26	35	3	½
25	16	729 910 107	10	0,012	32	41	3	¾
32	10	729 910 108	10	0,020	40	47	3	1
40	10	729 910 109	10	0,035	49	55	3	1 ¼
50	10	729 910 110	10	0,060	61	65	3	1 ½
63	10	729 910 111	10	0,110	76	79	3	2
75	10	729 910 112	10	0,145	87	92	4	2 ½
90	10	729 910 113	10	0,241	104	107	5	3
110	10	729 910 114	5	0,566	131	132	5	4
140	10	729 910 116	2	0,813	162	159	7	5
160	10	729 910 117	2	1,176	183	180	8	6
200	10	729 910 119	1	1,511	221	221	9	8
225	10	729 910 120	1	2,537	253	248	10	8
250	6	729 910 121	1	4,058	284	284	16	9
280	6	729 910 122	1	6,043	321	314	16	10
315	6	729 910 123	1	8,100	356	348	16	12

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>