



## 3-dlg koppeling, SYGEF® Standaard, PVDF, zwart FPM, PN16

### uitvoering:

- materiaal: PVDF
- met lasmof metrisch
- dichtvlak met O-ring groef
- ingebouwd: O-ring nr. 49 41 00 FPM
- s.v.p. montagehandleiding in acht nemen

d (mm)	PN (bar)	code	gewicht (kg)	D (mm)	G (inch)	L1 (mm)	L2 (mm)	z1 (mm)	z (mm)
16	16	<b>735 510 105</b>	0,025	35	3/4	18	24	5	11
20	16	<b>735 510 106</b>	0,057	43	1	19	26	5	12
25	16	<b>735 510 107</b>	0,090	53	1 1/4	21	28	5	12
32	16	<b>735 510 108</b>	0,118	60	1 1/2	23	30	5	12
40	16	<b>735 510 109</b>	0,195	74	2	25	34	5	14
50	16	<b>735 510 110</b>	0,244	82	2 1/4	28	39	5	16
63	16	<b>735 510 111</b>	0,403	100	2 3/4	32	47	5	20

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>