



overgangsmof, SYGEF® Standaard, PVDF, binnendraad - Rp, PN16

uitvoering:

- materiaal: PVDF
- met lasmof en cilindrische binnendraad - Rp
- aansluiting alleen voor kunststof draad
- geen PVDF aantastende draadafdichtingspasta gebruiken
- let op de juiste montage

d	Rp	PN	code	SP	gewicht	L	s	z
(mm)	(inch)	(bar)			(kg)	(mm)	(mm)	(mm)
20	½	16	735 910 206	10	0,030	34	32	5
25	¾	16	735 910 207	10	0,036	38	36	6
32	1	16	735 910 208	10	0,067	43	46	7
40	1 ¼	16	735 910 209	10	0,100	47	55	7
50	1 ½	16	735 910 210	10	0,135	54	65	9
63	2	16	735 910 211	5	0,217	62	80	9

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>