




T-stuk 90°, PP-H, S5/SDR11

uitvoering:

- materiaal: PP-H
- voor conventioneel stompassen conform DVS 2207
- IR = infrarood (IR Plus®) compatibel kies lasparameters: PP-H

¹ materiaal: PP-R



d (mm)	FM	Code	gewicht (kg)	L (mm)	L1 (mm)	e (mm)	
20	IR	727 208 506	0,011	38	24	1,9	
25	IR	727 208 507	0,018	42	26	2,3	
32	IR	727 208 508	0,032	46	26	2,9	
40	IR	727 208 509	0,062	51	23	3,7	
50	IR	727 208 510	0,105	58	22	4,6	
63	IR	727 208 511	0,186	66	20	5,8	
75	IR	727 208 512	0,293	75	20	6,8	
90	IR	727 208 513	0,521	90	20	8,2	
110	IR	727 208 514	0,928	110	20	10,0	
125	IR	727 208 515	1,347	125	25	11,4	
140	IR	727 208 516	1,923	140	28	12,7	
160	IR	727 208 517	2,844	160	28	14,6	
180	IR	727 208 568	4,844	194	74	16,4	
200	IR	727 208 519	5,579	200	35	18,2	
225	IR	727 208 520	7,812	220	35	20,5	
250	--	727 208 571	12,380	276	92	22,7	
280	--	727 208 572	17,735	318	110	25,4	
315	--	727 208 573	18,214	353	118	28,6	
1	355	--	727 208 524	31,100	345	105	32,2
1	400	--	727 208 525	40,900	365	105	36,3
1	450	--	727 208 526	60,300	425	135	40,9
1	500	--	727 208 527	81,900	470	155	45,4

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>