




3-dlg overgangskoppeling, PVC-C/RVS, metrisch - Rp

uitvoering:

- wartelmoer: PVC-C
- inschroefdeel: PVC-C lijm of metrisch
- inlegdeel: RVS WN 1.4404 (316L) met parallelle binnendraad Rp
- afdichting: O-ring EPDM 748 410 005-011



d (mm)	Rp (inch)	PN (bar)	EPDM Code	SP	gewicht (kg)	FPM Code	SP	gewicht (kg)
16	3/8	16	723 540 205	10	0,053	723 540 230	0	0,053
20	1/2	16	723 540 206	10	0,096	723 540 231	0	0,096
25	3/4	16	723 540 207	5	0,154	723 540 232	0	0,154
32	1	16	723 540 208	5	0,212	723 540 233	0	0,212
40	1 1/4	16	723 540 209	2	0,356	723 540 234	0	0,347
50	1 1/2	16	723 540 210	2	0,455	723 540 235	0	0,502
63	2	16	723 540 211	2	0,721	723 540 236	0	0,721

z1 (mm)	z2 (mm)	D (mm)	L (mm)	L1 (mm)	L2 (mm)	G (inch)	s (mm)
9	10	35	43	19	24	3/4	19
11	10	43	50	24	26	1	24
11	10	51	55	26	29	1 1/4	29
12	10	58	61	29	33	1 1/2	36
14	12	74	71	33	39	2	45
15	14	83	79	34	46	2 1/4	54
15	18	100	95	39	58	2 3/4	63

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>