




knie 90°, ABS metrisch

uitvoering:

- met lijm of metrisch en cilindrische binnendraad Rp
- versterkingsring RVS (A2)
- aansluiting voor kunststof of metalen draad
- let op juiste montage
- géén ABS aantastende draadafdichtingspasta gebruiken



d	Rp	PN	code	SP	gewicht	z1	z2	D	L
(mm)	(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)
20	½	10	729 100 206	10	0,018	11	14	30	27
25	¾	10	729 100 207	10	0,028	14	17	35	33
32	1	10	729 100 208	10	0,047	17	22	45	39
40	1 ¼	10	729 100 209	10	0,088	23	27	55	50
50	1 ½	10	729 100 210	5	0,128	27	36	62	58
63	2	10	729 100 211	5	0,233	33	46	75	73

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>