



## bocht 90°, PE100, SDR17/17,6

### Uitvoering:

- materiaal: PE100
- geschikt voor conventioneel stomplassen conform DVS 2207
- IR-lassen waar aangegeven, parameters: PE100

d (mm)	FM	code	gewicht (kg)	PF	L (mm)	L1 (mm)	R (mm)	e (mm)
50	IR	<b>753 018 635</b>	0,052	2 68 240 026	58	21	37	2,9
63	IR	<b>753 018 636</b>	0,087	2 68 240 026	66	21	45	3,6
75	IR	<b>753 018 737</b>	0,176	2 68 240 026	100	20	90	4,3
90	IR	<b>753 018 738</b>	0,245	2 68 240 026	100	20	90	5,1
110	IR	<b>753 018 739</b>	0,513	2 68 240 026	141	20	130	6,3
125	IR	<b>753 018 515</b>	0,556	2 68 240 022	125	28	116	7,3
140	IR	<b>753 018 516</b>	0,785	2 68 240 022	140	33	131	8,2
160	IR	<b>753 018 517</b>	1,156	2 68 240 022	160	33	151	9,4
180	IR	<b>753 018 518</b>	1,619	2 68 240 022	180	33	171	10,6
200	IR	<b>753 018 519</b>	2,208	2 68 240 022	200	33	190	11,7
225	IR	<b>753 018 520</b>	3,039	2 68 240 022	220	33	210	12,9
250		<b>753 018 521</b>	4,645	2 68 240 002	256	48	232	14,2
280		<b>753 018 522</b>	7,020	2 68 240 002	280	48	262	15,9
315		<b>753 018 523</b>	10,099	2 68 240 002	321	48	297	17,9
355		<b>753 020 824</b>	11,300	2 68 240 040	340	38	355	21,1
400		<b>753 020 825</b>	15,700	2 68 240 040	345	41	400	23,7
450		<b>753 020 826</b>	25,868	2 68 240 040	445	49	400	26,7
500		<b>753 020 827</b>	35,000	2 68 240 040	445	49	400	29,7

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>