



T-stuk 90°, PE100, SDR11

Uitvoering:

- materiaal: PE100
- geschikt voor conventioneel stomplassen conform DVS 2207
- IR-lassen waar aangegeven, parameters: PE100

| d (mm) | FM | code | gewicht (kg) | L (mm) | L1 (mm) | e (mm) |
|-----------|----|--------------------|-----------------|-----------|------------|-----------|
| 20 | IR | 753 208 606 | 0,013 | 38 | 24 | 1,9 |
| 25 | IR | 753 208 607 | 0,021 | 42 | 26 | 2,3 |
| 32 | IR | 753 208 608 | 0,042 | 46 | 26 | 2,9 |
| 40 | IR | 753 208 609 | 0,065 | 51 | 22 | 3,7 |
| 50 | IR | 753 208 610 | 0,111 | 58 | 22 | 4,6 |
| 63 | IR | 753 208 611 | 0,202 | 66 | 21 | 5,8 |
| 75 | IR | 753 208 612 | 0,312 | 75 | 20 | 6,8 |
| 90 | IR | 753 208 613 | 0,553 | 90 | 20 | 8,2 |
| 110 | IR | 753 208 614 | 1,002 | 110 | 20 | 10,0 |
| 125 | IR | 753 208 615 | 1,509 | 125 | 25 | 11,4 |
| 140 | IR | 753 208 616 | 2,105 | 140 | 28 | 12,7 |
| 160 | IR | 753 208 617 | 3,085 | 160 | 28 | 14,6 |
| 180 | IR | 753 208 668 | 5,062 | 190 | 70 | 16,4 |
| 200 | IR | 753 208 619 | 5,982 | 200 | 35 | 18,2 |
| 225 | IR | 753 208 620 | 8,090 | 220 | 35 | 20,5 |
| 250 | | 753 208 671 | 13,326 | 272 | 90 | 22,7 |
| 280 | | 753 208 672 | 20,458 | 313 | 108 | 25,4 |
| 315 | | 753 208 673 | 27,400 | 348 | 114 | 28,6 |
| 355 | | 753 208 624 | 32,600 | 345 | 105 | 32,3 |
| 400 | | 753 208 625 | 42,900 | 365 | 105 | 36,4 |
| 450 | | 753 208 626 | 63,300 | 425 | 135 | 40,9 |
| 500 | | 753 208 627 | 86,000 | 470 | 155 | 45,5 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>