

Specificatieblad


valid from: 26-2-16



3-delige overgangskoppeling, ABS/RVS metrisch - Rp

uitvoering:

- wartelmoer: ABS
- inschroefdeel: ABS lijmmof metrisch
- inlegdeel: RVS WN 1.4404 (316L) met parallelle binnendraad Rp
- afdichting: O-ring EPDM 748 410 006-011



PN (bar)	Rp (inch)	d (mm)	EPDM Code	SP	gewicht (kg)	z1 (mm)	z2 (mm)	D (mm)	L (mm)	L1 (mm)	L2 (mm)	G (inch)	s (mm)
10	½	20	729 540 206	10	0,096	11	10	43	50	24	26	1	24
10	¾	25	729 540 207	5	0,154	11	10	51	55	26	29	1 1/4	29
10	1	32	729 540 208	5	0,212	12	10	58	61	29	33	1 1/2	36
10	1 ¼	40	729 540 209	2	0,356	14	12	74	71	33	39	2	45
10	1 ½	50	729 540 210	2	0,443	15	14	83	79	34	46	2 1/4	54
10	2	63	729 540 211	2	0,721	15	18	100	95	39	58	2 3/4	63

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>