



## T-stuk 90° reductie, PVC-U metrisch

d (mm)	d1 (mm)	PN (bar)	d-d (inch)	code	SP	gewicht (kg)	z (mm)	z1 (mm)	D (mm)	L (mm)	L1 (mm)
25	20	16		721 200 134	10	0,038	14	14	33	33	30
32	20	16		721 200 141	10	0,061	17	17	41	39	33
32	25	16		721 200 138	10	0,063	17	17	41	39	36
40	20	16		721 200 155	10	0,103	23	23	50	49	39
40	25	16		721 200 151	10	0,107	23	23	50	49	42
40	32	16		721 200 147	10	0,109	23	23	50	49	45
50	20	16		721 200 009	5	0,179	28	28	62	59	44
50	25	16		721 200 010	5	0,183	28	28	62	59	47
50	32	16		721 200 164	5	0,189	28	28	62	59	50
50	40	16		721 200 161	5	0,208	28	28	62	59	54
63	25	16		721 200 011	10	0,332	35	34	77	73	53
63	32	16		721 200 178	5	0,336	35	34	77	73	56
63	40	16		721 200 174	5	0,347	35	34	77	73	60
63	50	16		721 200 170	5	0,354	35	34	77	73	65
75	32	16		721 200 181	9	0,535	40	41	92	84	63
75	40	16		721 200 182	9	0,555	40	41	92	84	67
75	50	16		721 200 183	8	0,541	40	41	92	84	72
75	63	16		721 200 184	8	0,570	40	41	92	84	79
90	32	16		721 200 142	6	0,855	46	55	110	97	77
90	50	16		721 200 144	6	0,907	46	55	110	97	86
90	63	16		721 200 145	5	0,931	46	55	110	97	93
90	75	16		721 200 146	5	0,959	46	55	110	97	99
110	32	16		721 200 135	3	1,441	56	67	133	117	89
110	50	16		721 200 136	3	1,471	56	67	133	117	98
110	63	16		721 200 132	3	1,522	56	65	133	117	103
110	75	16		721 200 133	3	1,543	56	65	133	117	109
110	90	16		721 200 137	3	1,634	56	65	133	117	116
125	50	16		721 200 139	4	1,970	64	75	151	133	106
125	90	16		721 200 140	4	2,200	64	75	151	133	126
140	50	16		721 200 148	1	3,235	72	82	172	148	113
140	75	16	5 - 2 ½	721 200 149	1	3,319	72	78	172	148	122
140	110	16		721 200 150	1	3,422	72	74	172	148	135
160	110	16		721 200 152	1	4,305	81	81	192	167	142
200	110	10		721 200 153	1	8,782	107	131	232	213	192
200	160	10		721 200 154	1	8,036	107	106	232	213	192
225	110	10		721 200 156	1	10,619	120	143	257	239	204
225	160	10		721 200 157	1	9,760	120	119	257	239	205
250	160	10		721 200 159	1	14,520	132	151	282	263	237
250	200	10		721 200 162	1	12,213	132	131	282	263	237
280	160	10		721 200 165	1	18,402	120	180	318	266	266
280	225	10		721 200 167	1	16,145	120	148	318	266	268
315	160	6		721 200 169	1	22,189	120	197	356	284	283
315	225	6		721 200 172	1	20,154	120	165	356	284	284
400	225	6		721 200 176	1	40,000	163	258	442	369	377
400	315	6		721 200 180	1	35,000	163	213	442	369	377

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland  
Phone +41 -(0)52-631 1111

# Data sheet

valid from: 9-1-17

---



e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>