



DN10/15 - 50



**kogelkraan type 546, SYGEF® Standaard, PVDF met inserts met moflaseind, metrisch**

**uitvoering:**

- materiaal: PVDF
- radiaal in- en uitbouwbaar
- kogelafdichting uit PTFE
- geïntegreerde draadbussen (inserts) voor de bevestiging van de afsluiter
- z-maat, inlegdeel en wartelmoer zijn niet compatibel met type 346

**optioneel:**

- individuele configuratie van de afsluiter
- multifunctie-module met geïntegreerde eindschakelaars
- stelaandrijvingen pneumatisch en elektrisch

d (mm)	DN (mm)	PN (bar)	kv-waarde ( $\Delta p=1$ bar) (L/min)	FPM code	SP	gewicht (kg)
16	10	16	71	<b>175 546 051</b>	1	0,200
20	15	16	185	<b>175 546 052</b>	1	0,205
25	20	16	350	<b>175 546 053</b>	1	0,310
32	25	16	700	<b>175 546 054</b>	1	0,460
40	32	16	1000	<b>175 546 055</b>	1	0,780
50	40	16	1600	<b>175 546 056</b>	1	1,110
63	50	16	3100	<b>175 546 057</b>	1	2,150

d (mm)	D (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	L6 (mm)	M	inch bena- dering (inch)
16	50	57	27	12	110	77	56		25	32	45	M6	¾
20	50	57	27	12	120	77	56	130	25	32	45	M6	½
25	58	67	30	12	139	97	65	150	25	39	58	M6	¾
32	68	73	36	12	150	97	71	160	25	39	58	M6	1
40	84	90	44	15	170	128	85	180	45	54	74	M8	1 ¼
50	97	97	51	15	190	128	89	200	45	54	74	M8	1 ½
63	124	116	64	15	220	152	101	230	45	66	87	M8	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>