



3-delige overgangskoppeling, PVC-U/RVS metrisch - Rp

uitvoering:

- wartelmoer: PVC-U
- inschroefdeel: PVC-U lijmmof metrisch
- inlegdeel: RVS WN 1.4404 (316L) met parallelle binnendraad Rp
- afdichting: O-ring EPDM 748 410 005-011

Rp (inch)	d (mm)	PN (bar)	EPDM Code	SP	gewicht (kg)	FPM Code	SP	gewicht (kg)
3/8	16	16	721 540 205	10	0,053	721 540 230	0	0,053
1/2	20	16	721 540 206	10	0,096	721 540 231	0	0,096
3/4	25	16	721 540 207	5	0,154	721 540 232	0	0,134
1	32	16	721 540 208	5	0,212	721 540 233	0	0,212
1 1/4	40	16	721 540 209	2	0,356	721 540 234	0	0,343
1 1/2	50	16	721 540 210	2	0,455	721 540 235	0	0,455
2	63	16	721 540 211	2	0,730	721 540 236	0	0,721

G (inch)	z1 (mm)	z2 (mm)	D (mm)	L (mm)	L1 (mm)	L2 (mm)	s (mm)
3/8	9	10	35	43	19	24	19
1	11	10	43	50	24	26	24
1 1/4	11	10	51	55	26	29	29
1 1/2	12	10	58	61	29	33	36
2	14	12	72	71	33	39	45
2 1/4	15	14	83	79	34	46	54
2 3/4	15	18	100	95	39	58	63

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>