



knie 45°, ABS metrisch

- >d225 - maximum temperatuur: +40°C

d (inch)	d (mm)	PN (bar)	code	SP gewicht (kg)	inch bena- dering (inch)	z (mm)	D (mm)	L (mm)
	20	16	729 150 106	10	0,009	½	5	25
	25	16	729 150 107	10	0,013	¾	6	31
	32	10	729 150 108	10	0,026	1	8	40
	40	10	729 150 109	10	0,044	1 ¼	10	49
	50	10	729 150 110	5	0,079	1 ½	12	61
	63	10	729 150 111	10	0,143	2	14	76
2 ½	75	10	729 150 112	5	0,225	2 ½	17	89
	90	10	729 150 113	4	0,363	3	20	107
	110	10	729 150 114	10	0,567	4	28	131
5	140	10	729 150 116	1	1,175	5	32	162
	160	10	729 150 117	4	1,713	6	36	185
	200	10	729 150 119	1	2,546	8	43	225
	225	10	729 150 120	1	3,162	8	49	250
	250	6	729 150 121	1	6,139	9	60	282
	280	6	729 150 122	1	10,500	10	66	318
	315	6	729 150 123	1	14,600	12	74	356

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>