



3-delige overgangskoppeling, PVC-U/RVS metrisch - met laseind

uitvoering:

- inschroefdeel: PVC-U lijmmof metrisch
- inlegdeel: RVS 1.4404 (316L) met laseind
- wartelmoer: RVS WN 1.4404 (316L)
- afdichting: O-ring EPDM 748 410 005-011

d (mm)	d1 (mm)	PN (bar)	EPDM Code	SP	gewicht (kg)	FPM Code	SP	gewicht (kg)
16	17	16	721 545 505	10	0,101	721 545 530	0	0,101
20	21	16	721 545 506	10	0,176	721 545 531	0	0,168
25	27	16	721 545 507	5	0,204	721 545 532	0	0,198
32	34	16	721 545 508	5	0,313	721 545 533	0	0,313
40	42	16	721 545 509	2	0,493	721 545 534	0	0,493
50	48	16	721 545 510	2	0,566	721 545 535	0	0,605
63	60	16	721 545 511	2	0,902	721 545 536	0	0,902

d (mm)	G (inch)	z (mm)	L (mm)	L1 (mm)	L2 (mm)	e (mm)	s (mm)
16	¾	28	42	18	24	1,6	32
20	1	32	48	22	26	2,0	41
25	1 ¼	33	52	23	29	2,0	46
32	1 ½	36	58	26	33	2,0	55
40	2	38	64	26	39	2,0	68
50	2 ¼	42	73	28	46	2,0	74
63	2 ¾	50	88	32	58	2,6	88

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>