



bocht 90°, PE100, SDR11

Uitvoering:

- materiaal: PE100
- geschikt voor conventioneel stomplassen conform DVS 2207
- IR-lassen waar aangegeven, parameters: PE100

d (mm)	FM	code	gewicht (kg)	PF	L (mm)	L1 (mm)	R (mm)	e (mm)
20	IR	753 018 706	0,007	2 68 240 006	38	23	15	1,9
25	IR	753 018 707	0,013	2 68 240 006	42	23	19	2,3
32	IR	753 018 708	0,025	2 68 240 006	46	22	24	2,9
40	IR	753 018 709	0,041	2 68 240 006	51	21	30	3,7
50	IR	753 018 710	0,065	2 68 240 006	58	21	37	4,6
63	IR	753 018 711	0,124	2 68 240 006	66	21	45	5,8
75	IR	753 018 712	0,246	2 68 240 006	100	20	90	6,8
90	IR	753 018 713	0,355	2 68 240 006	100	20	90	8,2
110	IR	753 018 714	0,757	2 68 240 006	141	25	130	10,0
125	IR	753 018 715	0,818	2 68 240 002	125	28	116	11,4
140	IR	753 018 716	1,148	2 68 240 002	140	33	116	12,7
160	IR	753 018 717	1,699	2 68 240 002	160	33	151	14,6
180	IR	753 018 718	2,394	2 68 240 002	180	33	171	16,4
200	IR	753 018 719	3,264	2 68 240 002	200	33	190	18,2
225	IR	753 018 720	4,535	2 68 240 002	220	33	210	20,5
250		753 018 621	6,713	2 68 240 002	256	48	232	22,7
280		753 018 622	9,885	2 68 240 002	282	48	262	25,4
315		753 018 623	14,158	2 68 240 002	321	48	297	28,6
355		753 021 024	17,200	2 68 240 040	380	38	355	32,3
400		753 021 025	31,100	2 68 240 040	434	41	400	36,3
450		753 021 026	38,300	2 68 240 040	445	49	400	40,9
500		753 021 027	47,300	2 68 240 040	445	49	400	45,4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>