


kraagbus, PVC-C metrisch, dichtvlak gegroefd



uitvoering:

- afdichting: vlakke pakking EPDM 748 400 306-320
- flens: 727 700 406-420, 727 700 206-220, 721 700 006-020
- afdichting: profielflensafdichting EPDM 748 440 706-720, FPM 749 440 706-720

opmerking:

* eventuele aanschuiningbuis nodig bij vlinderkleppen type 037/038/039

d (mm)	DN (mm)	PN (bar)	Code	SP	gewicht (kg)	z (mm)	D (mm)	D1 (mm)	L (mm)	L1 (mm)	
20	15	16	723 790 106	10	0,011	3	27	34	21	6	
25	20	16	723 790 107	10	0,018	3	33	41	24	7	
32	25	16	723 790 108	10	0,027	3	41	50	27	7	
40	32	16	723 790 109	10	0,032	3	50	61	30	8	
50	40	16	723 790 110	10	0,054	3	61	73	34	8	
63	50	16	723 790 111	10	0,097	3	76	90	41	9	
75	65	16	723 790 112	10	0,168	3	91	106	47	10	
90	80	16	723 790 113	10	0,265	5	108	125	56	11	
110	100	16	723 790 114	10	0,441	5	131	150	66	12	
*	160	150	16	723 790 117	12	1,139	5	188	213	91	16
*	200	200	10	723 790 119	2	1,630	6	224	250	112	24
	225	200	10	723 790 120	2	1,860	6	248	274	125	25

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>