



Barrel nipple ABS Inch BS

Model:

- With solvent cement spigots on both sides
- For quick connections between fittings
- For the shortest possible distance between fittings
- Overall length $L = 2 \times \text{socket length}$

PN (bar)	d (inch)	d (mm)	Code	SP	Weight (kg)	L (mm)	closest inch (inch)
10	3/8		729 901 905	0	0.002	28	
10	1/2		729 901 906	0	0.004	32	
10	3/4		729 901 907	0	0.008	38	
10	1		729 901 908	0	0.015	44	
10	1 1/4		729 901 909	0	0.027	52	
10	1 1/2		729 901 910	0	0.050	62	
10	2		729 901 911	0	0.098	76	
10	2 1/2	75	729 900 912	30	0.095	88	2 1/2
10	3		729 901 913	0	0.266	102	
10	4		729 901 914	0	0.476	122	
10	5		729 900 916	0	0.001	152	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
 Phone +41 -(0)52-631 1111
 e-mail: info.ps@georgfischer.com
 Internet: <http://www.gfps.com>