



voorlaskraag ABS
gecombineerd dichtvlak vlak en gegroefd, Inch BS

uitvoering:

- Gasket: flange gasket EPDM code no. 748 400 306-320, FPM code no. 749 400 306-320

d (inch)	PN (bar)	Code	SP	gewicht (kg)	D1 (mm)	D (mm)	L (mm)	L1 (mm)	z (mm)
½	15	729 791 106	10	0,007	34	27	21	6	3
¾	15	729 791 107	0	0,011	41	33	24	7	3
1	15	729 791 108	10	0,018	50	41	27	7	3
1 ¼	15	729 791 109	10	0,027	61	50	32	8	3
1 ½	15	729 791 110	10	0,043	73	61	33	8	3
2	15	729 791 111	5	0,083	90	76	41	9	3
2 ½	10	729 790 112	10	0,116	106	91	47	10	3
3	15	729 791 113	20	0,187	125	108	56	11	5
4	15	729 791 115	20	0,309	155	136	69	12	5
5	10	729 790 116	6	0,535	188	165	81	14	5
6	12	729 791 117	10	0,912	217	198	96	16	5
8	9	729 791 120	2	1,470	274	248	122	20	6

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>