




3-dlg overgangskoppeling PVC-U/malleabel gegalvaniseerd, metrisch - R

uitvoering:

- wartelmoer: PVC-U
- inschroefdeel: PVC-U lijmmof metrisch
- inlegdeel: malleabel met konische buitendraad R
- afdichting: O-ring EPDM 748 410 006-014; d90 748 410 248



d	R	PN	Code	SP	gewicht	D	L	L1	L2	z	G	s
(mm)	(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(inch)	(mm)
20	¾	16	721 530 806	10	0,107	43	66	40	26	50	1	25
25	¾	16	721 530 807	5	0,159	51	72	43	29	53	1 1/4	31
32	1	16	721 530 808	5	0,213	58	80	48	33	58	1 1/2	38
40	1 ¼	16	721 530 809	2	0,426	72	95	57	39	69	2	48
50	1 ½	16	721 530 810	2	0,528	83	104	59	46	73	2 1/4	54
63	2	16	721 530 811	5	0,863	100	118	62	58	80	2 3/4	67
75	2 ½	10	721 530 812	2	1,441	127	137	75	62	93	Tr 108x5	85
90	3	10	721 530 813	1	1,873	150	149	80	69	99	Tr 128x5	96

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>