



vaste flens, PVC-U metrisch, dichtvlak gegroefd

uitvoering:

- met lijmmof metrisch
- aansluitmaten volgens: ISO 7005 PN 10, EN 1092 PN 10, DIN 2501 PN 10, BS 4504 PN 10
- flensboring PN10

* gecombineerde flens, aansluitmaten volgens DIN 2501 PN 10 en ANSI B 16.5
d75 - d110: boutgat als lange uitvoering

AL = aantal gaten

d	DN	d	PN	Code	SP	gewicht	
(mm)	(mm)	(inch)	(bar)			(kg)	
20	15		16	721 740 106	50	0,100	
25	20		16	721 740 107	0	0,130	
32	25		16	721 740 108	0	0,185	
40	32		16	721 740 109	0	0,306	
50	40		16	721 740 110	0	0,368	
63	50		16	721 740 111	0	0,513	
*	75	65	2 ½	10	721 740 112	10	0,536
*	90	80	3	10	721 740 113	16	0,710
*	110	100	4	10	721 740 114	12	0,941
*	140	125	5	10	721 740 116	1	1,395
*	160	150	6	10	721 740 117	1	2,029

d	D	D1	D1	D1	D2	D3	z	H	H1	AL	SC
(mm)	(mm)	(mm)	max.	min.	(mm)	(mm)	(mm)	(mm)	(mm)		
			(mm)	(mm)							
20	95	65			27	14	3	12	19	4	M12
25	105	75			33	14	3	13	22	4	M12
32	115	85			41	14	3	14	25	4	M12
40	140	100			51	18	3	17	29	4	M16
50	150	110			62	18	3	17	34	4	M16
63	165	125			77	18	3	20	41	4	M16
*	75	185	140	144	91	19	3	21	47	4	M16
*	90	200	153	159	108	19	5	22	56	8	M16
*	110	220	181	191	131	24	5	24	66	8	M20
*	140	250	215		165	23	5	28	91	8	M20
*	160	285	240		188	23	5	30	91	8	M20

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>