





T-stuk 90° reductie, PP-H, S8,3/SDR17,6

uitvoering:

- materiaal: PP-H
- conventioneel stomplassen conform DVS 2207
- IR-lassen waar aangegeven

* met IR gelaste reductie

* aftakking SDR11



| | d (mm) | d1 (mm) | FM | code | SP | gewicht (kg) | e (mm) | e1 (mm) | L (mm) | L1 (mm) | L2 (mm) | L3 (mm) |
|---|-----------|------------|----|-------------|----|-----------------|-----------|------------|-----------|------------|------------|------------|
| * | 63 | 32 | IR | 727 208 301 | 10 | 0,120 | 3,6 | 2,9 | 65 | 70 | 25 | 25 |
| | 63 | 50 | IR | 727 208 302 | 10 | 0,124 | 3,6 | 2,9 | 65 | 70 | 25 | 25 |
| * | 75 | 32 | IR | 727 208 303 | 5 | 0,178 | 4,3 | 2,9 | 70 | 75 | 25 | 25 |
| | 75 | 50 | IR | 727 208 304 | 5 | 0,182 | 4,3 | 2,9 | 70 | 75 | 25 | 25 |
| | 75 | 63 | IR | 727 208 305 | 5 | 0,190 | 4,3 | 3,6 | 70 | 75 | 25 | 25 |
| | 90 | 50 | IR | 727 208 307 | 5 | 0,305 | 5,1 | 2,9 | 80 | 85 | 25 | 25 |
| | 90 | 63 | IR | 727 208 308 | 5 | 0,315 | 5,1 | 3,6 | 80 | 85 | 25 | 25 |
| | 90 | 75 | IR | 727 208 309 | 5 | 0,320 | 5,1 | 4,3 | 80 | 85 | 25 | 25 |
| * | 110 | 32 | IR | 727 208 310 | 5 | 0,489 | 6,3 | 2,9 | 90 | 95 | 30 | 25 |
| | 110 | 50 | IR | 727 208 311 | 5 | 0,490 | 6,3 | 2,9 | 90 | 95 | 30 | 25 |
| | 110 | 63 | IR | 727 208 312 | 5 | 0,491 | 6,3 | 3,6 | 90 | 95 | 30 | 25 |
| | 110 | 75 | IR | 727 208 313 | 5 | 0,500 | 6,3 | 4,3 | 90 | 95 | 30 | 25 |
| | 110 | 90 | IR | 727 208 314 | 5 | 0,514 | 6,3 | 5,1 | 90 | 95 | 30 | 25 |
| 1 | 125 | 63 | IR | 727 208 315 | 1 | 1,680 | 7,1 | 3,6 | 125 | 232 | 30 | 16 |
| 1 | 125 | 90 | IR | 727 208 316 | 1 | 1,680 | 7,1 | 5,1 | 125 | 228 | 30 | 22 |
| 1 | 125 | 110 | IR | 727 208 317 | 1 | 1,680 | 7,1 | 6,3 | 125 | 224 | 30 | 28 |
| 1 | 140 | 75 | IR | 727 208 318 | 1 | 1,700 | 8,0 | 4,3 | 140 | 258 | 35 | 19 |
| 1 | 140 | 90 | IR | 727 208 319 | 1 | 1,800 | 8,0 | 5,1 | 140 | 250 | 35 | 22 |
| 1 | 140 | 110 | IR | 727 208 320 | 1 | 2,000 | 8,0 | 6,3 | 140 | 245 | 35 | 28 |
| | 160 | 63 | IR | 727 208 321 | 1 | 1,535 | 9,1 | 3,6 | 142 | 135 | 50 | 30 |
| | 160 | 75 | IR | 727 208 322 | 1 | 1,550 | 9,1 | 4,3 | 142 | 135 | 50 | 30 |
| | 160 | 90 | IR | 727 208 323 | 1 | 1,567 | 9,1 | 5,1 | 142 | 135 | 50 | 30 |
| | 160 | 110 | IR | 727 208 324 | 1 | 1,577 | 9,1 | 6,3 | 142 | 135 | 50 | 30 |
| 1 | 160 | 125 | IR | 727 208 325 | 1 | 1,600 | 9,1 | 7,1 | 160 | 279 | 43 | 32 |
| 1 | 200 | 160 | IR | 727 208 335 | 1 | 5,624 | 11,4 | 9,1 | 200 | 256 | 70 | 40 |
| 1 | 200 | 180 | IR | 727 208 336 | 1 | 2,200 | 11,4 | 10,2 | 200 | 354 | 70 | 45 |
| | 225 | 90 | IR | 727 208 338 | 1 | 3,350 | 12,8 | 5,1 | 155 | 165 | 40 | 30 |
| | 225 | 110 | IR | 727 208 339 | 1 | 3,330 | 12,8 | 6,3 | 155 | 165 | 40 | 30 |
| | 225 | 160 | IR | 727 208 341 | 1 | 3,427 | 12,8 | 9,1 | 155 | 165 | 40 | 30 |
| 1 | 250 | 160 | | 727 208 343 | 1 | 2,800 | 14,2 | 9,1 | 276 | 425 | 92 | 45 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>