



3-weg kogelkraan type 543 horizontaal/L-boring, SYGEF® Standaard met lasmof, metrisch

uitvoering:

- materiaal: PVDF
- radiaal in- en uitbouwbaar (inlegdeel en wartelmoer zijn compatibel met type 546)
- kogelafdichting uit PTFE
- achteraf uit te breiden met elektrische of pneumatische stelaandrijving
- stelbereik 360°, zonder slagbegrenzing
- slagbegrenzing voor stelbereik 90° wordt meegeleverd; kan optioneel op verschillende posities worden vastgeklikt
- geïntegreerde draadbussen (inserts) voor de bevestiging van de afsluiter
- leveringsstand A-C geopend; zie schakelschema

d (mm)	DN (mm)	PN (bar)	kv-waarde ($\Delta p=1$ bar) (L/min)	FPM code	gewicht (kg)
16	10	10	50	175 543 011	0,281
20	15	10	75	175 543 012	0,290
25	20	10	150	175 543 013	0,461
32	25	10	280	175 543 014	0,654
40	32	10	480	175 543 015	1,199
50	40	10	620	175 543 016	1,647
63	50	10	1230	175 543 017	3,227

d (mm)	D (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	L6 (mm)	M (mm)	z (mm)	z1 (mm)	inch bena- dering (inch)
16	50	57	28	8	110	77	72	36	25	32	45	6	82	41	$\frac{3}{8}$
20	50	57	28	8	112	77	72	36	25	32	45	6	82	41	$\frac{1}{2}$
25	58	67	32	8	129	97	85	43	25	39	58	6	97	49	$\frac{3}{4}$
32	68	73	36	8	146	97	98	49	25	39	58	6	110	55	1
40	84	90	45	9	170	128	118	59	45	54	74	8	132	66	$1 \frac{1}{4}$
50	97	97	51	9	193	128	135	68	45	54	74	8	151	76	$1 \frac{1}{2}$
63	124	116	65	9	244	152	176	88	45	66	87	8	188	94	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>