




PROGEF standaard 3-dlg koppeling PP-H/messing, metrisch Rp

uitvoering:

- wartelmoer: PP-H
- inlegdeel met lasmof PP-H metrisch
- inlegdeel: messing met parallel binnendraad Rp
- afdichting: O-ring EPDM nr. 48 41 00



Rp (inch)	PN (bar)	d (mm)	Code	SP	gewicht (kg)	D (mm)	L1 (mm)	L (mm)	L2 (mm)	s (mm)	z1 (mm)	z2 (mm)	G (inch)
½	10	20	727 550 506	10	0,091	48	22	48	26	25	7	10	1
¾	10	25	727 550 507	5	0,152	58	25	53	28	30	9	10	1 1/4
1	10	32	727 550 508	5	0,194	65	27	57	30	36	8	10	1 1/2
1 ¼	10	40	727 550 509	1	0,317	79	31	65	34	46	10	12	2
1 ½	10	50	727 550 510	2	0,436	91	35	74	39	55	13	14	2 1/4
2	10	63	727 550 511	5	0,774	105	40	87	47	65	14	18	2 3/4

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>