


Fittings with short Spigot



Code: 006

- Tee
- short spigot
- flame retardant
- injection moulded
- Butt-welding
- PPs grey

Dimension	Code	Detail	da(OD) mm	s mm	z mm	L mm	L3 mm	Weight
110	17.006.0110.33	110X3,4 SDR33 ISO S-16	110	3,4	109	223	33	0.44
160	17.006.0160.33	160X4,9 SDR33 ISO S-16	160	4,9	173	346	57	1.74
180	17.006.0180.33	180X5,5 SDR33 ISO S-16	180	5,5	186	372	57	1.407
200	17.006.0200.33	200X6,2 SDR33 ISO S-16	200	6,2	205	410	57	3.24
225	17.006.0225.33	225X6,9 SDR33 ISO S-16	225	6,9	222	448	57	4.42
250	17.006.0250.33	250X7,7 SDR33 ISO S-16	250	7,7	237	475	70	3.83
280	17.006.0280.33	280X8,6 SDR33 ISO S-16	280	8,6	270	540	80	8.56
315	17.006.0315.33	315X9,7 SDR33 ISO S-16	315	9,7	277	558	80	8.554
20	17.006.0020.11	20X1,9 SDR11 ISO S-5	20	1,9	34	68	17,5	0.019
25	17.006.0025.11	25X2,3 SDR11 ISO S-5	25	2,3	40	80	20,5	0.03
32	17.006.0032.11	32X2,9 SDR11 ISO S-5	32	2,9	45	90	20,5	0.035
40	17.006.0040.11	40X3,7 SDR11 ISO S-5	40	3,7	50	100	20,5	0.068
50	17.006.0050.11	50X4,6 SDR11 ISO S-5	50	4,6	60	120	23	0.112
63	17.006.0063.11	63X5,8 SDR11 ISO S-5	63	5,8	72	144	25	0.221
75	17.006.0075.11	75X6,8 SDR11 ISO S-5	75	6,8	75	152	15	0.393
90	17.006.0090.11	90X8,2 SDR11 ISO S-5	90	8,2	105	213	38	0.695
110	17.006.0110.11	110X10,0 SDR11 ISO S-5	110	10	122	253	51	1.18
140	17.006.0140.11	140X12,7 SDR11 ISO S-5	140	12,7	152	305	53	2.36
160	17.006.0160.11	160X14,6 SDR11 ISO S-5	160	14,6	173	346	57	3.45