



Ball valve type 104 PVC-U 100-230V With solvent cement sockets metric

Model:

- Voltage 100-230 V, 50-60 Hz
- Control range 90°<
- For easy installation and removal
- Integrated stainless steel mounting inserts

d (mm)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	EPDM Code	FPM Code	SP	GP	Weight (kg)
16	10	10	70	199 104 002	199 104 012	1	0	0.995
20	15	10	185	199 104 003	199 104 013	1	0	0.995
25	20	10	350	199 104 004	199 104 014	1	0	1.050
32	25	10	700	199 104 005	199 104 015	1	0	1.120
40	32	10	1000	199 104 006	199 104 016	1	0	1.290
50	40	10	1600	199 104 007	199 104 017	1	0	2.010
63	50	10	3100	199 104 008	199 104 018	1	0	2.395

d (mm)	H (mm)	L (mm)	Type of actuator	B (mm)
16	194	178.5	10Nm	50
20	194	178.5	10Nm	50
25	207	186.0	10Nm	58
32	217	192.5	10Nm	68
40	236	204.5	10Nm	84
50	275	208.5	20Nm	97
63	307	221.5	20Nm	124

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>