



knie 45°, PE100, SDR17,6

uitvoering:

- IR-lassen waar aangegeven, parameters: PE100
- geschikt voor conventioneel stomplassen conform DVS 2207

d (mm)	FM	code	SP	gewicht (kg)	PF	L (mm)	L1 (mm)	e (mm)
50	--	753 158 535	10	0,045	2 68 240 008	42	26	2,9
63	--	753 158 536	10	0,091	2 68 240 008	47	29	3,6
75	--	753 158 412	10	0,125	2 68 240 008	49	29	4,7
90	--	753 158 413	5	0,198	2 68 240 028	57	34	5,6
110	IR	753 158 414	5	0,375	2 68 240 028	70	43	6,9
125	IR	753 158 540	5	0,542	2 68 240 028	79	48	7,1
140	IR	753 158 541	1	0,784	2 68 240 023	88	55	8,0
160	IR	753 158 542	1	1,190	2 68 240 023	100	60	9,1
200	IR	753 158 544	1	2,331	2 68 240 023	124	75	11,4
225	IR	753 158 545	1	3,282	2 68 240 023	140	85	12,8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>