




bocht 90°, PP-H S8,3/SDR17,6

uitvoering:

- materiaal: PP-H
- conventioneel stomplassen conform DVS 2207
- IR-lassen waar aangegeven

* Material:PP-R



d (mm)	FM	code	gewicht (kg)	L (mm)	L1 (mm)	R (mm)	e (mm)
50	IR	727 018 635	0,050	58	21	37	2,9
63	IR	727 018 636	0,081	66	21	45	3,6
75	IR	727 018 637	0,164	100	20	90	4,3
90	IR	727 018 638	0,241	100	20	90	5,1
110	IR	727 018 639	0,484	141	25	130	6,3
125	IR	727 018 415	0,556	125	28	116	7,1
140	IR	727 018 416	0,785	140	33	131	8,0
160	IR	727 018 417	1,156	160	33	151	9,1
180	IR	727 018 418	1,619	180	33	171	10,2
200	IR	727 018 419	2,208	200	33	190	11,4
225	IR	727 018 420	3,039	220	33	210	12,8
250		727 018 421	4,359	256	48	232	14,2
280		727 018 422	6,696	286	48	262	15,9
315		727 018 423	8,580	321	48	297	17,9
*	355	727 018 549	13,300	355	15	355	20,1
*	400	727 018 550	18,615	400	25	400	22,7

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>