




T-stuk 90°, PP-H, S8,3/SDR17,6

uitvoering:

- IR = infrarood (IR Plus®) compatibel kies lasparameters: PP-H
- materiaal: PP-H
- voor conventioneel stompassen conform DVS 2207

¹ materiaal: PP-R



d (mm)	FM	Code	gewicht (kg)	L (mm)	L1 (mm)	e (mm)
50	IR	727 208 535	0,079	59	26	2,9
63	IR	727 208 536	0,178	73	31	3,6
75	IR	727 208 412	0,212	75	20	4,3
90	IR	727 208 413	0,396	90	20	5,1
110	IR	727 208 414	0,705	110	20	6,3
125	IR	727 208 540	1,077	125	30	7,1
140	IR	727 208 541	1,478	140	35	8,0
160	IR	727 208 542	2,264	160	43	9,1
180	IR	727 208 543	3,343	194	70	10,2
200	IR	727 208 544	4,902	210	70	11,4
225	IR	727 208 545	6,889	235	82	12,8
250		727 208 546	9,325	276	92	14,2
280		727 208 547	13,463	318	110	15,9
315		727 208 548	18,000	353	118	17,9
1	355	727 208 424	20,800	345	105	20,1
1	400	727 208 425	27,200	365	105	22,7
1	450	727 208 426	47,300	425	135	26,7
1	500	727 208 427	54,800	470	155	29,7

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>