




T-stuk 90° reductie, PE100, SDR17,6

uitvoering:

- materiaal: PE100
- geschikt voor conventioneel stomplassen conform DVS 2207
- IR-lassen waar aangegeven, parameters: PE100
- 5 bar gas / 10 bar water

* aftakking SDR11



	d (mm)	d1 (mm)	FM	code	gewicht (kg)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	e (mm)	e1 (mm)
*	63	32	--	753 208 301	0,163	65	70	25	25	3,6	2,9
	63	50	--	753 208 302	0,171	65	70	25	25	3,6	2,9
*	75	32	--	753 208 303	0,231	70	75	25	25	4,3	2,9
	75	50	--	753 208 304	0,250	70	75	25	25	4,3	2,9
	75	63	--	753 208 305	0,263	70	75	25	25	4,3	3,6
	90	50	--	753 208 307	0,411	80	85	25	25	5,1	2,9
	90	63	--	753 208 308	0,329	80	85	25	25	5,1	3,6
	90	75	--	753 208 309	0,339	80	85	25	25	5,1	4,3
*	110	32	IR	753 208 310	0,643	90	95	30	25	6,3	2,9
	110	50	IR	753 208 311	0,655	90	95	30	25	6,3	2,9
	110	63	IR	753 208 312	0,516	90	95	30	25	6,3	3,6
	110	75	IR	753 208 313	0,521	90	95	30	25	6,3	4,3
	110	90	IR	753 208 314	0,529	90	95	30	25	6,3	5,1
	160	63	IR	753 208 321	2,103	142	135	50	30	9,1	3,6
	160	75	IR	753 208 322	2,142	142	135	50	30	9,1	4,3
	160	90	IR	753 208 323	1,668	142	135	50	30	9,1	5,1
	160	110	IR	753 208 324	1,687	142	135	50	30	9,1	6,3
	225	90	IR	753 208 338	3,439	155	165	40	30	12,8	5,1
	225	110	IR	753 208 339	3,448	155	165	40	30	12,8	6,3
	225	160	IR	753 208 341	3,471	155	165	40	30	12,8	9,1

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>