



T-stuk 90°, reductie, PE100 SDR17/17,6

- moulded
- lang spie-eind uitvoering
- 5 bar gas / 10 bar water

d (mm)	d1 (mm)	code	SP	gewicht (kg)	z (mm)	z1 (mm)	L (mm)	L1 (mm)	e (mm)	e1 (mm)
90	50	753 201 827	15	0,630	275	117	79	55	5,4	3,0
90	63	753 200 829	15	0,560	275	123	79	63	5,4	3,8
225	140	753 200 855	1	8,780	286	132	80	75	5,4	4,5
110	63	753 200 828	10	1,010	318	147	82	63	6,6	3,8
110	75	753 200 831	1	0,891	315	152	84	70	6,6	4,5
110	90	753 200 832	10	0,941	318	158	82	79	6,6	5,4
125	110	753 200 833	1	1,399	334	168	84	83	7,4	6,6
160	63	753 200 834	1	1,950	330	130	86	63	9,5	3,8
160	75	753 200 835	2	1,932	343	180	98	74	9,5	4,5
160	90	753 200 836	8	1,972	410	188	98	79	9,5	5,4
160	110	753 200 837	1	2,716	410	195	98	82	9,5	6,6
180	90	753 200 844	1	3,250	422	204	134	97	10,7	5,4
180	160	753 200 838	1	3,557	411	205	105	94	10,7	9,5
200	63	753 201 873	1	6,800	500	190	122	63	11,9	3,8
200	90	753 201 874	1	6,900	500	207	122	79	11,9	5,4
200	110	753 201 875	1	5,097	500	215	122	82	11,9	6,6
200	160	753 201 876	1	7,400	500	234	122	98	11,9	9,5
225	75	753 200 839	0	7,128	555	277	120	70	13,4	4,5
225	90	753 200 840	3	4,732	555	226	127	80	13,4	5,4
225	110	753 200 841	1	4,700	555	235	127	82	13,4	6,6
225	160	753 200 842	3	5,922	555	253	127	98	13,4	9,5
225	180	753 200 843	1	7,211	550	280	120	105	13,4	10,7
250	110	753 201 878	1	9,400	575	242	130	82	14,8	6,6
250	160	753 201 879	1	9,800	575	261	130	98	14,8	9,5
315	110	753 200 851	1	15,621	695	277	150	82	18,7	6,6
315	160	753 200 852	1	12,200	695	296	150	102	18,7	9,5
315	225	753 200 853	1	14,869	650	335	170	145	18,7	13,4
315	250	753 200 854	1	15,500	695	325	150	130	18,7	14,8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>