




## T-stuk 90° recht met lasbare aftakking (kit)

- PE100 SDR 11 (ISO S5)
- 10 bar gas / 16 bar water
- geïntegreerde kleminrichting (tot d63)
- 4 mm stekkeraansluiting
- begrensd lasindicator
- wordt geleverd als kit, met ELGEF® Plus mof of ELGEF® Plus reductie



d (mm)	d2 (mm)	code	SP	gewicht (kg)	d1 (mm)	L (mm)	L1 (mm)	z (mm)	z1 (mm)	H (mm)
20	20	<b>753 201 606</b>	1	0,161	35	90	34	11	92	67
25	25	<b>753 201 607</b>	1	0,122	35	90	34	11	92	70
32	32	<b>753 201 608</b>	1	0,201	44	102	36	15	100	74
40	32	<b>193 281 006</b>	1	0,288	54	120	39	21	127	95
40	40	<b>753 201 609</b>	1	0,285	54	120	39	21	114	82
50	32	<b>193 281 007</b>	1	0,364	66	135	43	24	144	108
50	40	<b>193 281 008</b>	1	0,407	66	135	43	24	140	104
50	50	<b>753 201 610</b>	1	0,389	66	135	43	24	126	90
63	32	<b>193 280 997</b>	1	0,550	81	152	48	28	173	125
63	40	<b>193 281 009</b>	1	0,566	81	152	48	28	169	121
63	50	<b>193 281 010</b>	1	0,628	81	152	48	28	165	117
63	63	<b>753 201 611</b>	1	0,615	81	152	48	28	150	102
90	63	<b>193 281 011</b>	1	1,311	112	202	61	41	182	120
90	90	<b>753 201 613</b>	1	1,342	112	202	61	41	146	84
110	90	<b>193 281 012</b>	1	2,343	136	242	65	56	200	127
110	110	<b>753 201 614</b>	1	2,329	136	242	65	56	161	88
125	90	<b>193 281 013</b>	1	3,146	151	256	75	53	214	132
125	125	<b>753 201 615</b>	1	2,960	151	256	75	53	174	92
160	110	<b>193 281 030</b>	1	7,443	196	325	92	71	271	168
160	160	<b>753 201 617</b>	1	6,359	196	325	92	71	206	103
180	125	<b>193 281 031</b>	1	9,654	225	344	90	82	330	190
180	180	<b>753 201 618</b>	1	8,561	225	344	90	82	250	110

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>