




reductie met geïntegreerde kleminrichting

- PE100 SDR 11 (ISO S5)
- 10 bar gas / 16 bar water
- 4 mm stekeraansluiting
- begrensd lasindicator



d (mm)	d2 (mm)	Code	SP	gewicht (kg)	d1 (mm)	L (mm)	L1 (mm)	L2 (mm)	z (mm)
25	20	753 901 639	1	0,051	35	74	34	34	6
32	20	753 901 640	1	0,056	44	79	33	36	10
32	25	753 901 641	1	0,062	44	79	33	36	10
40	20	753 901 644	1	0,069	54	88	33	39	15
40	25	753 901 645	1	0,084	54	88	33	39	15
40	32	753 901 646	1	0,095	54	88	33	39	13
50	32	753 901 651	1	0,124	66	96	35	43	18
50	40	753 901 652	1	0,119	66	96	39	43	14
63	32	753 901 656	1	0,158	81	105	35	48	23
63	40	753 901 657	1	0,176	81	105	39	48	19
63	50	753 901 658	1	0,176	81	105	43	48	15

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>