



PROGEF Standard
Ball valve type 104 24V
With fusion sockets metric

Model:

- Material: PP-H
- Voltage 24 V AC/DC
- Control range 90°<
- For easy installation and removal
- Integrated stainless steel mounting inserts

d (mm)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	EPDM Code	FPM Code	SP	Weight (kg)
16	10	10	70	199 104 542	199 104 552	1	0.965
20	15	10	185	199 104 543	199 104 553	1	0.965
25	20	10	350	199 104 544	199 104 554	1	1.010
32	25	10	700	199 104 545	199 104 555	1	1.055
40	32	10	1000	199 104 546	199 104 556	1	1.180
50	40	10	1600	199 104 547	199 104 557	1	1.860
63	50	10	3100	199 104 548	199 104 558	1	2.115

H (mm)	L (mm)	Type of actuator	B (mm)
194	178.5	10Nm	50
194	78.5	10Nm	50
207	185.5	10Nm	58
217	190.5	10Nm	68
236	198.5	10Nm	84
275	203.5	20Nm	97
307	214.0	20Nm	124

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>