


3-delige overgangskoppeling ABS/messing, metrisch R

uitvoering:

- wartelmoer: ABS
- inschroefdeel: ABS lijmmof metrisch
- ingedeel: messing met konische buitendraad R
- afdichting: O-ring EPDM 748 410 006-011



d (mm)	R (inch)	PN (bar)	Code	SP	gewicht (kg)	D (mm)	L (mm)	L1 (mm)	L2 (mm)	z (mm)	G (inch)	s (mm)
20	½	10	729 550 906	10	0,123	43	63	37	26	47	1	25
25	½	10	729 550 957	5	0,185	51	66	37	29	48	1 1/4	30
25	¾	10	729 550 907	5	0,175	51	71	42	29	52	1 1/4	30
25	1	10	729 550 967	5	0,293	51	75	46	29	57	1 1/4	30
32	½	10	729 550 958	5	0,283	58	70	37	33	48	1 1/2	36
32	¾	10	729 550 968	5	0,283	58	75	42	33	53	1 1/2	36
32	1	10	729 550 908	5	0,374	58	79	46	33	57	1 1/2	36
40	1 ¼	10	729 550 909	2	0,503	72	91	52	39	65	2	46
50	1 ½	10	729 550 910	2	0,640	83	102	56	46	71	2 1/4	55
63	2	10	729 550 911	2	1,019	100	125	67	58	87	2 3/4	65

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>