


3-delige overgangskoppeling ABS/messing, metrisch Rp

uitvoering:

- wartelmoer: ABS
- inschroefdeel: ABS lijmof metrisch
- inlegdeel: messing met parallelle binnendraad Rp
- afdichting: O-ring EPDM 748 410 006-011



PN (bar)	Rp (inch)	d (mm)	Code	SP	gewicht (kg)	z1 (mm)	s (mm)	L2 (mm)	L (mm)	G (inch)	z2 (mm)	D (mm)	L1 (mm)
10	½	20	729 550 506	10	0,084	7	25	26	48	1	10	43	22
10	¾	25	729 550 507	5	0,134	9	30	29	54	1 1/4	11	51	25
10	1	32	729 550 508	5	0,179	8	36	33	60	1 1/2	11	58	27
10	1 ¼	40	729 550 509	2	0,327	10	48	39	70	2	13	72	31
10	1 ½	50	729 550 510	2	0,452	14	55	46	81	2 1/4	21	83	35
10	2	63	729 550 511	2	0,674	14	65	58	98	2 3/4	21	100	40

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>