


Specificatieblad

valid from: 9-1-17



T-stuk 90°, ABS metrisch

- > d225 - maximum temperatuur: +40°C



PN (bar)	d (inch)	d (mm)	Code	SP	gewicht (kg)	inch bena- dering (inch)	z (mm)	D (mm)	L (mm)
16		20	729 200 106	10	0,015	½	11	25	27
16		25	729 200 107	10	0,025	¾	14	31	33
10		32	729 200 108	10	0,042	1	17	40	39
10		40	729 200 109	10	0,078	1 ¼	21	49	47
10		50	729 200 110	5	0,134	1 ½	26	61	57
10		63	729 200 111	5	0,255	2	34	76	72
10	2 ½	75	729 200 112	6	0,404	2 ½	40	90	84
10		90	729 200 113	4	0,664	3	47	107	98
10		110	729 200 114	6	1,010	4	55	133	116
10	5	140	729 200 116	1	2,570	5	71	169	147
10		160	729 200 117	1	3,752	6	81	193	167
10		200	729 200 119	1	4,446	8	101	225	207
10		225	729 200 120	1	6,860	8	114	256	233
6		250	729 200 121	1	11,189	9	132	282	263
6		280	729 200 122	1	11,989	10	152	318	298
6		315	729 200 123	1	20,000	12	168	356	332

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>