


PROGEF Standaard 3-dlg overgangskoppeling PP-H/messing metrisch R (PN10)

uitvoering:

- inlegdeel: messing met konische buitendraad R
- afdichting: O-ring EPDM
- wartelmoer: PP-H
- inschroefdeel: lasmof PP-H metrisch



d (mm)	R (inch)	Code	SP	gewicht (kg)	L (mm)	L1 (mm)	L2 (mm)	D (mm)	s (mm)	G (inch)	z (mm)
20	½	727 550 906	10	0,130	63	37	26	48	25	1	47
25	½	727 550 957	5	0,203	65	37	28	58	30	1 1/4	47
25	¾	727 550 907	5	0,203	70	42	28	58	30	1 1/4	52
25	1	727 550 967	5	0,318	99	46	30	58	30	1 1/4	81
32	½	727 550 958	5	0,298	67	37	30	65	36	1 1/2	47
32	¾	727 550 968	5	0,298	72	42	30	65	36	1 1/2	52
32	1	727 550 908	5	0,389	76	46	30	65	36	1 1/2	56
40	1 ¼	727 550 909	5	0,493	86	52	34	79	46	2	64
50	1 ½	727 550 910	2	0,650	95	56	39	91	55	2 1/4	70
63	2	727 550 911	8	1,123	114	67	47	105	65	2 3/4	85

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>