



Model Sample

HÜRNER WhiteLine HWT 400 Manual

This member of the **HÜRNER** workshop technology series is used for the manufacture of segments made of PE, PP, PVDF and ships **fitted with narrow aluminium clamping jaws**.

The design of the machine is such that segments up to O.D. 400 mm with any SDR ratio can be processed.

The system was developed under the the machinery directive 2006/42/EC as amended and is set on a welded and bolted, totally heavy-duty support frame resistant to warping by design. Both the movable carriage of the system and the console carrying the

heating element and the facing tool travel on precision-engineered, heavy load-bearing trapeze-shaped guides constructed with precision-matched runner blocks. The PTFE-coated heating element managed by a microcontroller turns conveniently and effortlessly around its axis for insertion and removal. The two clamping jaws can be swiveled by up to 2 x 22.5 deg. on both sides and feature horizontal adjustability, to allow for compensating any misalignments. The facing tool has a rugged chain drive mechanism and can be inserted and fastened between the component butts easy as ABC using a gas-pressurized cylinder.

HÜRNER HWT 400 Manual characteristics

P/N	406-000-008
Technical specs	
Voltage	3 ph., N, PE, 400 V AC \pm 10 %
Frequency	50/60 Hz
Overall rated power	9 kW
Heating el. rated power	5 kW
Facing tool rated power	1.85 kW
Hydr. unit rated power	1.5 kW
Dimensions, weights	
Dimensions (W x D x H)	approx. 1100 x 1500 x 1600 mm
Weight, incl. clamping jaws	557 kg
Operating specs	
Heating element temperature range	max. 290 °C max. 555 °F
Hydr. pressure range	max. 120 bar max. 1740 psi
Ambient temperature (operating)	\pm 0 °C thru + 60 °C 32 °F thru 140 °F
Ambient temperature (stored)	- 10 °C thru + 70 °C 15 °F thru 160 °F

Operating range		
Straight pipe Segments	90 - 400 mm	
Approvals, quality, ingress protection	CE, ISO 9001 : 2015, IP54 (optionally IP64), WEEE reg. no. DE 74849106, RoHS-compliant	
Accessories	User's manual DE, EN, FR, ES, RU, operator ID card, tools	
Optional components		
Replacement blade	P/N	315-109-026
Additional cylinder	P/N	200-260-410
Welding neck support	P/N	200-604-355
Add-in reducers 90 mm for short radius 22.5 deg.	P/N	406-146-000
Add-in reducers 90 mm for short radius 30 deg.	P/N	406-147-000
Add-in reducers 110 mm for short radius 22.5 deg.	P/N	406-148-000
Add-in reducers 110 mm for short radius 30 deg.	P/N	406-149-000
Angle support bracket	P/N	406-155-000

04.2021

You want to learn more about us?

Feel free to ask for a meeting on our premises. Detailed information on the company and on our product range is also available on-line at www.huerner.de



HÜRNER

S C H W E I S S T E C H N I K

HÜRNER Schweisstechnik GmbH

Nieder-Ohmener Str. 26
35325 Mücke

GERMANY

Ph +49 6401 9127 0
Fx +49 6401 9127 39
E-Mail info@huerner.de
Internet: www.huerner.de

HÜRNER Welding Technology NZ Ltd

12 Croskery Road
Papakura
Auckland 2110
NEW ZEALAND

Ph +64 9 299 3640
Fx +64 9 299 3740
E-Mail r.gruen@extra.co.nz
Internet: www.huerner.co.nz

HÜRNER Schweisstechnik Gulf L.L.C

Damascus Street, Al Qusais 4
DUBAI
P.O.Box 233586
UNITED ARAB EMIRATES

Ph +971 4 2584886
Fx +971 4 2584887
E-Mail info@hurnergulf.ae
Internet: www.huerner.de