



Bocht 30° (zonder segmenten)

sok aansluiting, $r = d$

tubular bends 30° (without segments)

socket connection, $r = d$

	PVC, PVC-C, PVC-UV					PPs, PP, PE, PPs-el, PVDF				
d	L	L1	H	s	kg	L	L1	H	s	kg
0050	30	25	20	3,5	0,1	30	25	20	3,0	0,1
0063	30	25	20	3,5	0,1	30	25	20	3,0	0,1
0075	40	35	25	3,5	0,1	40	35	25	3,0	0,1
0090	40	35	30	3,5	0,1	40	35	30	3,0	0,1
0110	50	40	55	4,0	0,2	50	40	40	3,5	0,2
0125	50	40	60	5,0	0,2	50	40	45	3,0	0,2
0140	50	40	70	4,0	0,3	50	40	50	3,5	0,3
0160	50	40	65	3,5	0,3	50	40	55	3,0	0,3
0180	60	50	85	3,5	0,4	60	50	60	3,0	0,4
0200	60	50	85	3,0	0,5	60	50	65	3,0	0,5
0225	60	50	105	4,0	0,6	60	50	70	4,0	0,6
0250	60	50	105	4,0	0,8	60	50	75	3,5	0,7
0280	60	50	125	6,0	0,9	60	50	85	4,0	1,0
0315	60	50	140	5,0	1,4	60	50	95	5,0	1,4
0355	60	50	155	5,0	1,6	60	50	105	5,0	1,7
0400	70	60	175	6,0	1,9	70	60	120	6,0	2,7
0450	70	60	195	4,0	3,4	70	60	135	6,0	4,1
0500	70	65	215	5,0	3,9	70	60	155	6,0	4,8
0560	-	-	-	-	-	100	90	170	6,0	5,1
0600	80	65	170	5,0	5,6	-	-	-	-	-
0630	-	-	-	-	-	115	100	190	8,0	7,5
0700	110	90	210	7,0	14,0	-	-	-	-	-
0710	-	-	-	-	-	115	95	210	8,0	8,9
0800	115	100	235	7,0	18,0	115	100	350	10,0	18,5
0900	115	100	265	8,0	18,0	115	100	390	8,0	18,5
1000	115	100	265	8,0	18,0	115	100	430	8,0	18,5