



GS Flens voor pakkingen

sok aansluiting

gs socket flanges for gasket

PVC, PVC-C, PVC-UV								
d	D	B	s	k	d1	d2	Anzahl d2	kg
0050	100	8	3,0	80	46	7	4	0,1
0063	120	8	3,0	100	59	7	4	0,1
0075	135	8	3,0	115	71	7	4	0,1
0090	150	8	3,0	130	86	7	4	0,2
0110	170	8	4,0	150	106	7	4	0,2
0125	185	8	4,0	165	121	7	8	0,2
0140	200	8	4,0	175	136	7	8	0,3
0160	230	8	4,0	200	156	7	8	0,3
0180	250	8	4,0	225	176	7	8	0,4
0200	270	8	4,0	240	196	7	8	0,4
0225	295	8	4,0	265	221	7	8	0,4
0250	320	10	4,0	290	246	7	12	0,6
0280	360	10	4,0	325	274	9	12	0,7
0315	395	10	4,5	350	309	9	12	0,8
0355	435	10	6,0	400	349	9	12	1,0
0400	480	10	6,5	445	394	9	16	1,1

PPs, PP, PE, PPs-el, PVDF								
d	D	B	s	k	d1	d2	Anzahl d2	kg
0050	100	8	3,0	80	46	7	4	0,1
0063	120	8	3,0	100	59	7	4	0,1
0075	135	8	3,0	115	71	7	4	0,1
0090	150	8	3,0	130	86	7	4	0,1
0110	170	8	4,0	150	106	7	4	0,1
0125	185	8	4,0	165	121	7	8	0,2
0140	200	8	4,0	175	136	7	8	0,2
0160	230	8	4,0	200	156	7	8	0,2
0180	250	8	4,0	225	176	7	8	0,2
0200	270	8	4,0	240	196	7	8	0,3
0225	295	8	4,0	265	221	7	8	0,3
0250	320	10	4,0	290	246	7	12	0,4
0280	360	10	4,0	325	274	9	12	0,5
0315	395	10	4,5	350	309	9	12	0,6
0355	435	10	6,0	400	349	9	12	0,7
0400	480	10	6,5	445	394	9	16	0,8