



Verlopen symmetrisch 315/110 t/m 450/400 mm
Sok aansluiting

reducers symmetrical 315/110 to 450/400 mm
socket connection

	PVC, PVC-C, PVC-UV						PPs, PP, PE, PPs-el, PVDF					
d1 - d2	L	L1	L2	L3	s	kg	L	L1	L2	L3	s	kg
0315-0110	470	50	40	380	3,0	0,1	470	50	40	380	4,0	1,0
0315-0125	460	50	40	370	3,0	1,4	460	50	40	370	4,0	1,3
0315-0140	430	50	40	340	3,0	1,4	435	50	40	345	4,0	1,2
0315-0160	405	50	40	315	3,0	1,3	395	50	40	305	4,0	1,2
0315-0180	355	50	40	265	3,0	1,2	360	50	40	270	4,0	1,1
0315-0200	330	50	50	230	3,0	1,2	335	50	50	235	4,0	1,1
0315-0225	285	50	50	185	3,0	1,0	285	50	50	185	4,5	1,1
0315-0250	240	50	50	140	4,0	1,3	240	50	50	140	4,5	0,9
0315-0280	195	50	50	85	4,0	1,0	185	50	50	85	4,5	0,8
0355-0160	480	50	50	380	4,0	2,3	485	50	50	385	5,0	1,9
0355-0180	445	50	50	345	4,0	2,2	445	50	50	345	5,0	1,8
0355-0200	405	50	50	305	3,0	1,5	410	50	50	310	5,0	1,7
0355-0225	355	50	50	255	3,0	1,4	360	50	50	260	5,0	1,6
0355-0250	315	50	50	215	4,0	1,7	315	50	50	215	4,5	1,3
0355-0280	255	50	50	155	4,0	1,5	260	50	50	160	5,0	1,3
0355-0315	200	60	50	90	4,0	1,2	205	60	50	95	5,0	1,0
0400-0160	575	60	50	465	4,0	3,0	580	60	50	470	5,0	2,5
0400-0180	540	60	50	430	4,0	2,8	540	60	50	430	5,0	2,4
0400-0200	500	60	50	390	4,0	2,7	500	60	50	390	5,0	2,3
0400-0225	455	60	50	345	4,0	2,6	455	60	50	345	5,0	2,2
0400-0250	405	60	50	295	4,0	2,4	410	60	50	300	5,0	2,1
0400-0280	350	60	50	240	4,0	2,2	355	60	50	245	5,0	1,9
0400-0315	285	60	50	175	4,0	1,9	290	60	50	180	5,0	1,6
0400-0355	210	60	50	100	4,0	1,5	215	60	50	105	5,0	1,3
0450-0200	595	60	50	485	4,0	3,6	600	60	50	490	6,0	3,6
0450-0225	545	60	50	435	4,0	3,4	550	60	50	440	6,0	3,4
0450-0250	500	60	50	390	4,0	3,2	505	60	50	395	6,0	3,3
0450-0280	445	60	50	335	4,0	3,0	450	60	50	340	6,0	3,0
0450-0315	380	60	50	370	4,0	2,7	385	60	50	275	6,0	2,7
0450-0355	305	60	50	195	4,0	2,3	310	60	50	200	6,0	2,3
0450-0400	230	60	60	110	4,0	1,8	235	60	60	115	6,0	1,9