



Verlopen symmetrisch 500/200 t/m 630/600 mm
Sok aansluiting

reducers symmetrical 500/200 to 630/600 mm
socket connection

	PVC, PVC-C, PVC-UV						PPs, PP, PE, PPs-el, PVDF					
d1 - d2	L	L1	L2	L3	s	kg	L	L1	L2	L3	s	kg
0500-0200	675	50	50	575	4,0	4,3	680	50	50	580	6,0	4,4
0500-0225	630	50	50	530	4,0	4,2	635	50	50	535	6,0	4,2
0500-0250	600	70	50	480	4,0	4,2	610	70	50	490	6,0	4,2
0500-0280	545	70	50	425	4,0	4,0	555	70	50	435	6,0	4,0
0500-0315	490	65	65	360	4,0	3,7	500	65	65	370	6,0	3,7
0500-0355	405	65	50	290	5,0	4,0	410	65	50	295	6,0	3,2
0500-0400	330	70	55	205	5,0	3,5	335	70	55	210	6,0	2,8
0500-0450	245	70	60	115	5,0	2,7	245	70	60	115	6,0	2,2
0560-0250	-	-	-	-	-	-	720	70	50	600	6,0	5,4
0560-0280	-	-	-	-	-	-	665	70	50	545	6,0	5,2
0560-0315	-	-	-	-	-	-	600	70	50	480	6,0	4,8
0560-0355	-	-	-	-	-	-	525	70	50	405	6,0	4,4
0560-0400	-	-	-	-	-	-	465	90	55	320	6,0	4,2
0560-0450	-	-	-	-	-	-	380	90	60	230	6,0	3,6
0560-0500	-	-	-	-	-	-	285	90	60	135	6,0	2,8
0600-0280	735	70	50	615	5,0	7,5	-	-	-	-	-	-
0600-0315	670	70	50	550	5,0	7,1	-	-	-	-	-	-
0600-0355	600	70	50	480	6,0	8,0	-	-	-	-	-	-
0600-0400	520	70	60	395	5,0	6,0	-	-	-	-	-	-
0600-0450	435	70	60	305	6,0	6,3	-	-	-	-	-	-
0600-0500	340	70	60	210	6,0	5,1	-	-	-	-	-	-
0600-0560	-	-	-	-	-	-	-	-	-	-	-	-
0630-0280	-	-	-	-	-	-	795	70	50	675	6,0	6,7
0630-0315	-	-	-	-	-	-	730	70	50	610	6,0	6,4
0630-0355	-	-	-	-	-	-	655	70	50	535	6,0	6,0
0630-0400	-	-	-	-	-	-	605	100	55	450	6,0	5,8
0630-0450	-	-	-	-	-	-	520	100	60	360	6,0	5,2
0630-0500	-	-	-	-	-	-	425	100	60	265	6,0	4,5
0630-0560	-	-	-	-	-	-	325	100	70	155	6,0	3,6