



## Verlopen asymmetrisch 500/200 bis 630/600 mm

Sok aansluiting

*reducers asymmetrical 500/200 to 630/600 mm*

*socket connection*

	PVC, PVC-C, PVC-UV							PPs, PP, PE, PPs-el, PVDF								
d1 x d2	L	L1	L2	L3	X	s	s1		L	L1	L2	L3	X	s	s1	
0500-0200	635	60	50	530	150	4,0	4,0		650	60	50	540	150,0	6,0	3,0	
0500-0225	590	60	50	485	138	4,0	4,0		605	60	50	495	137,5	6,0	3,5	
0500-0250	550	60	50	445	125	4,0	4,0		565	60	50	455	125,0	6,0	3,5	
0500-0280	495	60	50	390	110	4,0	4,0		505	60	50	399	110,0	6,0	4,0	
0500-0315	435	60	50	330	93	4,0	4,0		445	60	50	335	92,5	6,0	5,0	
0500-0355	375	60	50	265	73	4,0	4,0		380	60	50	275	72,5	6,0	5,0	
0500-0400	310	60	60	190	50	4,0	4,0		315	60	60	200	50,0	6,0	6,0	
0500-0450	215	60	60	100	25	4,0	4,0		220	60	60	105	25,0	6,0	6,0	
0560-0250	-	-	-	-	-	-	-		705	90	50	565	155,0	6,0	3,5	
0560-0280	-	-	-	-	-	-	-		650	90	50	505	140,0	6,0	4,0	
0560-0315	-	-	-	-	-	-	-		585	90	50	445	122,5	6,0	5,0	
0560-0355	-	-	-	-	-	-	-		525	90	50	385	102,5	6,0	5,0	
0560-0400	-	-	-	-	-	-	-		455	90	60	305	80,0	6,0	6,0	
0560-0450	-	-	-	-	-	-	-		360	90	60	215	55,0	6,0	6,0	
0560-0500	-	-	-	-	-	-	-		315	90	60	135	30,0	6,0	6,0	
0600-0280	685	70	50	565	160	5,0	3,0		-	-	-	-	-	-	-	
0600-0315	625	70	50	505	143	5,0	3,0		-	-	-	-	-	-	-	
0600-0355	560	70	50	440	123	5,0	4,0		-	-	-	-	-	-	-	
0600-0400	490	70	60	360	100	5,0	4,0		-	-	-	-	-	-	-	
0600-0450	405	70	60	280	75	5,0	4,0		-	-	-	-	-	-	-	
0600-0500	320	70	60	195	50	5,0	4,0		-	-	-	-	-	-	-	
0600-0560	-	-	-	-	-	-	-		-	-	-	-	-	-	-	
0630-0280	-	-	-	-	-	-	-		765	90	50	625	175,0	6,0	4,0	
0630-0315	-	-	-	-	-	-	-		705	90	50	565	157,5	6,0	5,0	
0630-0355	-	-	-	-	-	-	-		640	90	50	505	137,5	6,0	5,0	
0630-0400	-	-	-	-	-	-	-		575	90	60	425	115,0	6,0	6,0	
0630-0450	-	-	-	-	-	-	-		480	90	60	330	90,0	6,0	6,0	
0630-0500	-	-	-	-	-	-	-		395	90	60	250	65,0	6,0	6,0	
0630-0560	-	-	-	-	-	-	-		325	90	90	145	35,0	6,0	6,0	