



**Zadelstuk 90°, Sok aansluiting**

**saddle connection 90°, socket connection**

	PVC, PVC-C					PPs, PP, PE, PPs-el, PVDF						
d	L	L1	L2	s	kg	L	L1	L2	s	kg		
0050m	65	35	30	2,4	0,1	65	35	30	3,0	0,1		
0063m	80	35	33	3,0	0,2	80	35	33	3,0	0,1		
0075m	90	35	36	2,2	0,2	90	35	36	3,0	0,1		
0090m	100	35	39	2,7	0,2	100	35	39	3,0	0,2		
0110m	130	40	53	3,2	0,3	130	40	53	3,0	0,3		
0125m	145	40	56	1,8	0,4	145	40	56	3,0	0,3		
0140m	160	40	59	2,8	0,5	160	40	59	3,0	0,4		
0160m	185	40	73	3,2	0,8	185	40	73	3,0	0,5		
0180m	205	50	77	2,5	0,8	205	50	77	3,0	0,6		
0200m	225	50	81	2,5	1,0	225	50	81	3,0	0,8		
0225m	255	50	97	2,8	1,3	255	50	97	3,5	1,1		
0250m	280	50	102	2,9	1,6	280	50	102	3,5	1,3		
0280m	305	50	108	2,9	1,9	305	50	108	4,0	1,9		
0315m	340	50	115	2,9	2,4	340	50	115	5,0	2,8		
0355m	375	50	124	2,9	3,0	375	50	124	5,0	3,5		
0400m	415	60	133	3,2	4,0	415	60	133	6,0	5,3		
0450m	460	60	153	3,6	6,5	470	70	153	6,0	7,0		
0500m	505	60	164	4,0	8,0	515	70	164	6,0	9,8		
0560m	-	-	-	-	-	570	70	176	6,0	13,7		
0600m	620	65	194	5,0	14,0	-	-	-	-	-		
0630m	-	-	-	-	-	645	70	201	6,0	17,0		
0700m	710	80	265	6,0	24,0	-	-	-	-	-		
0710m	-	-	-	-	-	720	80	267	8,0	24,5		
0800m	800	100	286	6,3	33,0	800	100	286	8,0	30,0		

Bij bestelling diameter hoofdleiding opgeven.