

No. : GZIN1905021726CM



Date : May 13, 2019

Page: 1 of 7

CUSTOMER NAME:	JIANGSU PIVOT NEW DECORATIVE MATERIALS CO., LTD
ADDRESS:	PIVOT INDUSTRIAL PARK, HUASHI, JIANGYIN, JIANGSU, CHINA

Sample Name	:	Aluminum	composite	panel
-------------	---	----------	-----------	-------

Product Specification : 1220*2440*2/3/4

Other Information : IBOND

Above information and sample(s) was/were submitted and confirmed by the client. SGS, however, assumes no responsibility to verify the accuracy, adequacy and completeness of the sample information provided by client.

Date of Receipt	:	May 06, 2019
Testing Start Date	:	May 06, 2019
Testing End Date	:	May 10, 2019
Test result(s)	:	For further details, please refer to the following page(s) (Unless otherwise stated the results shown in this test report refer only to the sample(s) tested)

Signed for SGS-CSTC Standards Technical Services Co., Ltd. GZ Branch Testing Center

Tobby Yang Authorized signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/an/ferms-and-Conditions</u>. app. and. for electronic format documents, subject to its rimetation of its instance of this documents. This documents and this documents are the transaction framework of the instance of this document is the second of the company's sole responsibility is to its colument to the accument to its document is transaction from exercising all their rights and obligations under the transaction forgery or falsification of the company's sole responsibility is to its Cilent and this document. This document is expected to the document is unavaluand offenders may be presecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: to check the authenticity of testing / inspection report & certificate, please contact at testephone: (86-75) 8307 1443, or email: CN.Doccheck@sgs.com



No. : GZIN1905021726CM Date : May 13, 2019 Page: 2 of 7

Test Result Summary

EN 13501-1:2018 Fire classification of construction products and building elements-Part 1: Classification using data from reaction to fire tests		
elements-Part 1: Classification using data from reaction to fire tests		
ciencits i ar i. Classification using data nom reaction to me tests		

Summary:

1. For further details, please refer to the following page(s).



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions for the document.aspx. Attention is drawn to the limitation of italiation and just and by the Company's findings at the time of its Intervention only and within the limits of transaction from exercising all their rights and obligations under the transaction documents. This document is advised that information contained hereon reflects the Company's findings at the time of its Intervention only and within the limits of appearance of this document is and switch and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or regulated that the transaction check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@sgs.com



No. : GZIN1905021726CM Date : May 13, 2019 Page: 3 of 7

TESTS AND RESULTS

Test Conducted:

This test is conducted as per EN 13501-1:2018 Fire classification of construction products and building elements-Part 1: Classification using data from reaction to fire tests. And the test methods as following:

- 1. EN 13823:2010+A1:2014 Reaction to fire tests for building products-Building products excluding floorings exposed to the thermal attack by a single burning item.
- 2. EN ISO 11925-2:2010+AC:2011 Reaction to fire tests-Ignitability of building products subjected to direct impingement of flame-Part 2: Single-flame source test.

Mounting and fixing (For EN 13823:2010+A1:2014):

The specimen was tested free standing at a distance of at least 80 mm from the backing board. Both wings were clamped at the top and the bottom.

Test Results:

Test method	Parameter	Number of tests	Results
	FIGRA _{0.2MJ} (W/s)		127.0
	FIGRA _{0.4MJ} (W/s)		127.0
	THR _{600s} (MJ)		5.9
EN 13823:2010+A1:2014	SMOGRA (m ² /s ²)	3	1.2
	TSP _{600s} (m ²)		11.2
	LFS < edge of specimen		Yes
	Flaming particles or droplets		No
EN ISO 11925-	<i>F</i> s ≤ 150 mm		Yes
2:2010+AC:2011 Exposure = 30 s	Ignition of the filter paper	6	No

Remark:

FIGRA-Fire growth rate index used for classification purposes [W/s]

For the classes A2 and B, FIGRA_{0.2}MJ

For the classes C and D, $\mathsf{FIGRA}_{0.4}\mathsf{MJ}$

LFS-Lateral flame spread [m]

THR_{600s}-Total heat release within 600 s [MJ]

SMOGRA-Smoke growth rate [m²/s²]

TSP_{600s}-Total smoke production within 600 s [m²]



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Conditi</u>



No. : GZIN1905021726CM Date : May 13, 2019 Page: 4 of 7

Classification and direct field of application:

This classification has been carried out in accordance with EN 13501-1:2018.

Classification:

Fire behaviour		Smoke p	roduction		Flaming	droplets
С	—	S	1	,	d	0

Remark:

The classes with their corresponding fire performance are given in Table 1. Reaction to fire classification is based on the 7-step scale of A1 to F, where A1 is good and F is bad

Statement:

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use.

Warning:

This classification report does not represent type approval or certification of the product. The test laboratory has, therefore, play no part in sampling the product for the test, although it holds appropriate references to the manufacturer's factory production control that is aimed to be relevant to the samples tested and that will provide for their traceability.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms.and-Conditions.asp</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms.and-Conditions.Terms.a-bocument.sg</u>, Attention is drawn to the limitation of lability, indemnification and jurisdiction issues defined therein. Any holder of this document is addrave that information company and there on the second the second therein the second therein there of the second there on the second therein the second there of the second there on the second the s



No. : GZIN1905021726CM Date : May 13, 2019 Page: 5 of 7

Table 1 — Classes of reaction to fire performance for construction products excluding floorings and linear pipe thermal insulation products.

Class	Test method(Classification criteria	Additional classification	
A1 EN ISO 1182 ^a and EN ISO 1716		<i>∆T</i> ≤30°C, and <i>∆m</i> ≤50%, and t _f =0(i.e. no sustained flaming)	-		
		6	PCS≤2.0MJ/kg ^a and PCS≤2.0MJ/kg ^{bc} and PCS≤1.4MJ/m ^{2 d} and PCS≤2.0MJ/kg ^e	-	
	EN ISO 1182 ª or		<i>∆T</i> ≤50°C, and <i>∆m</i> ≤50%, and t _f ≤20 s	-	
A2	EN ISO 1716	and	PCS≤3.0MJ/kg ^a and PCS≤4.0MJ/m ² ^b and PCS≤4.0MJ/m ² ^d and PCS≤3.0MJ/kg ^e and	-	
	EN 13823		FIGRA≤120W/s and LFS <edge and<br="" of="" specimen="">THR_{600s}≤7.5MJ</edge>	Smoke production ^f and Flaming droplets/particles ^g	
В	EN 13823 and EN ISO 11925-2 ⁱ Exposure =30s		FIGRA≤120W/s and LFS <edge and<br="" of="" specimen="">THR600s≤7.5MJ</edge>	Smoke production ^f and	
			Fs≤150mm within 60 s	Flaming droplets/particles	
С	C EN 13823 and EN ISO 11925-2 i Exposure=30s		FIGRA≤250W/s and LFS <edge and<br="" of="" specimen="">THR600s≤15MJ</edge>	Smoke production ^f and	
			Fs≤150mm within 60 s	Flaming droplets/particles	
	EN 13823	and	FIGRA≤750W/s	Smoke production ^f and	
D	EN ISO 11925-2 ⁱ Exposure=30s		Fs≤150mm within 60 s	Flaming droplets/particles ^g	
E	EN ISO 11925-2 ¹ Exposure =15s		Fs≤150mm within 20 s	flaming droplets/particles h	
F	EN ISO 11925-2 Exposure =15s		Fs>150mm within 20 s	-	



Unless otherwise agreed in writing, this document is issued by the <u>Company suppresent</u>. If the <u>Conditions agreed is a consistent of the control of the co</u>



No. : GZIN1905021726CM Date : May 13, 2019 Page: 6 of 7

^a For homogeneous products and substantial components of non-homogeneous products.

^b For any external non-substantial component of non-homogeneous products.

^c Alternatively, any external non-substantial component having a PCS \leq 2,0 MJ/m², provided that the product satisfies the following criteria of EN 13823: FIGRA \leq 20 W/s, and LFS < edge of specimen, and THR_{600s} \leq 4,0 MJ, and s1, and d0.

^d For any internal non-substantial component of non-homogeneous products.

^e For the product as a whole.

^f In the last phase of the development of the test procedure, modifications of the smoke measurement system have been introduced, the effect of which needs further investigation. This may result in a modification of the limit values and/or parameters for the evaluation of the smoke production.

s1 = SMOGRA \leq 30m²/s² and TSP_{600s} \leq 50m² ; s2 = SMOGRA \leq 180m²/s² and TSP_{600s} \leq 200m²; s3 = not s1 or s2

^g d0 = No flaming droplets/ particles in EN 13823 within 600 s;

d1 = no flaming droplets/ particles persisting longer than 10 s in EN 13823 within 600 s; d2 = not d0 or d1.

Ignition of the paper in EN ISO 11925-2 results in a d2 classification.

- ^h Pass = no ignition of the paper (no classification);
- Fail = ignition of the paper (d2 classification).

ⁱ Under conditions of surface flame attack and, if appropriate to the end–use application of the product, edge flame attack.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed vorteal available on request or accessible at http://www.gs.com/en/Terms-and-Conditions.sept and, for electronic Format documents, subject to its dawn to the limitation of labits, indemnification and jurisdiction issues defined therein. Any holder of this document is advised to there any holder of this document is advised to the same of its intervention on and within the limits of a same and there any holder of this document is advised to the same of the intervention on and within the limits of advised the same of the intervention on and within the limits of advised the same of the intervention on and within the limits of appearance of this document is and obligations under the transaction of orgeny or falsification of the company. Any unauthorized alteration, forgery or falsification of the content or suppearance of this document is sundwit and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

148 kabu Road, Skinteh Pak, Exomatic Habniz District, Quangbou, China.
510663
1(86-20) 82155555
f (86-20) 8207500
exos.sgs.com



No. : GZIN1905021726CM Date : May 13, 2019 Page: 7 of 7

SAMPLE INFORMATION AND PICTURES

Thickness: About 3mm Mass per unit area: About 4.12kg/m²





 Before Test (EN 13823)
 After Test (EN 13823)

 Note: The above test was carried out by SGS-CSTC Standards Technical Services Co., Ltd. Shunde Branch.

 ******** End of report*******



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.app</u> and, for electronic format documents, subject to its drawn to the limitation of labels at <u>http://www.sgs.com/en/Terms-and-Conditions.app</u> and, for electronic format documents, subject to its drawn to the limitation of labels the Company's lindings at the time of its intervention only and within the limits of advised that information contained hereon reflects the Company's lindings at the time of its intervention only and within the limits of advised that information contained hereon reflects the Company's lindings at the time of its intervention only and within the limits of appearance of this document is and obligations under the transaction form exercising all their rights and obligations under the transaction forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (85-75) 8307 1443, or email: CN.Doccheck@gs.com

 Wiskuback3.com
 Katuback3.com
 510663
 (166-20) 82155555
 (86-20) 82075080
 www.sgs.com.nc