


Specificatieblad

valid from: 05-08-2024



mof, ABS metrisch

- > d225 - maximum temperatuur: +40°C

d (mm)	PN (bar)	Code	SP	gewicht (kg)	D (mm)	L (mm)	z (mm)	inch bena- dering (inch)
20	16	729 910 106	10	0,007	26	35	3	½
25	16	729 910 107	10	0,012	32	41	3	¾
32	10	729 910 108	10	0,020	40	47	3	1
40	10	729 910 109	10	0,035	49	55	3	1 ¼
50	10	729 910 110	10	0,060	61	65	3	1 ½
63	10	729 910 111	10	0,110	76	79	3	2
75	10	729 910 112	20	0,145	87	92	4	2 ½
90	10	729 910 113	10	0,241	104	107	5	3
110	10	729 910 114	5	0,566	131	132	5	4
140	10	729 910 116	2	0,813	162	159	7	5
160	10	729 910 117	2	1,176	183	180	8	6
200	10	729 910 119	1	1,511	221	221	9	8
225	10	729 910 120	1	2,537	253	248	10	8

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>