

**SIMONA® PE Platten, gepresst**

Dicke		DIN EN ISO 15527	
von	bis	Toleranz min.	Toleranz max.
mm	mm	mm	mm
10	≤ 20	- 0	+ 3,0
> 20	40	- 0	+ 5,0
> 40	60	- 0	+ 6,0
> 60	80	- 0	+ 8,0
> 80	100	- 0	+ 10,0
> 100	120	- 0	+ 12,0
> 120	150	- 0	+ 14,0
> 150	200	- 0	+ 16,0

**SIMONA® PE Platten, gepresst**

von besäumten Platten		
Länge / Breite	Toleranz min.	Toleranz max.
mm	mm	mm
< 1.000	- 0	+ 4,0
≥ 1.000	- 0	+ 10,0
≥ 2.000	- 0	+ 17,0
≥ 4.000	- 0	+ 25,0
≥ 6.000	- 0	+ 35,0

**SIMONA® PP Platten, gepresst**

Dicke		in Anlehnung an DIN EN ISO 15527	
von	bis	Toleranz min.	Toleranz max.
mm	mm	mm	mm
10	≤ 20	- 0	+ 3,0
> 20	40	- 0	+ 5,0
> 40	60	- 0	+ 6,0
> 60	80	- 0	+ 8,0
> 80	100	- 0	+ 10,0
> 100	120	- 0	+ 12,0
> 120	150	- 0	+ 14,0
> 150	200	- 0	+ 16,0

**SIMONA® PP Platten, gepresst**

von besäumten Platten		
Länge / Breite	Toleranz min.	Toleranz max.
mm	mm	mm
< 1.000	- 0	+ 4,0
≥ 1.000	- 0	+ 10,0
≥ 2.000	- 0	+ 17,0
≥ 4.000	- 0	+ 25,0
≥ 6.000	- 0	+ 35,0

**SIMONA® PVDF Platten, gepresst**

Dicke		in Anlehnung an DIN EN ISO 15527	
von	bis	Toleranz min.	Toleranz max.
mm	mm	mm	mm
10	≤ 20	- 0	+ 3,0
> 20	40	- 0	+ 5,0
> 40	60	- 0	+ 6,0
> 60	80	- 0	+ 8,0
> 80	100	- 0	+ 10,0
> 100	120	- 0	+ 12,0
> 120	150	- 0	+ 14,0
> 150	200	- 0	+ 16,0

**SIMONA® PVDF Platten, gepresst**

von besäumten Platten		
Länge / Breite	Toleranz min.	Toleranz max.
mm	mm	mm
< 1.000	- 0	+ 2,0
≥ 1.000	- 0	+ 4,0
≥ 2.000	- 0	+ 8,0
≥ 4.000	- 0	+ 16,0
≥ 6.000	- 0	+ 24,0